



## MATERIAL SAFETY DATA :

Product name	Synpol 105 X
Flash point <sup>0</sup> C. (Abel closed cup)	30
Flammability	Moderate fire risk
Toxicity	Mild toxicity by exposure and inhalation due to presence of very small quantity of polyamines.
Handling	Keep away from sources of ignition, provide all electric connections of flame-proof design. Wear safety glasses, rubber gloves and protective clothings.
Emergency treatment and measures	
1 Hygienic precautions	Adequate ventilations.
2 Hygienic treatments (First Aid)	Flush eyes thoroughly with water. Apply ophthalmic cortisone for conjunctivitis and keratities. Wash out contaminated skin with soap and water. Gastric lavage (stomach wash), if swallowed, followed by saline catharsis.
3 Fire precautions (in case of outbreaks)	Use dry chemical or carbon dioxide. Water spray may help to keep containers cool, to dilute leaked resins and to diffuse vapours.
Spills and leakage	Absorb liquid materials in sand and collect solid material and burn under hood in incinerator.
Disposal and waste treatment	Spray into furnace under controlled conditions.

### STORAGE :

Synpol 105 X should be stored in cool place under shade. The properties are so adjusted to have storage stability of minimum 6 months.

### PACKING :

25 kgs. M.S. drums, 50 kgs. Plastic carboys and 180 kgs. M.S. barrels.

### DISCLAIMER :

Information in this literature is to the best of our knowledge true and accurate. However, since conditions under which our products may be used are beyond our control, recommendations are made without warranty or guarantee.

Issue date : Jan. 2009

Riv-04