

Model	Roller Dimensions (without padding) MM/Inches	Normal Roller speed at 50 Hz	AC Inverter (VFD) Variable Speed	Connections		Heating (Thermostatically Controlled)		Total electricity consumption		Suction pipe dimensions exhaust side	Overall dimensions (W x D x H) in mm	Net weight/Shipping weight
				Drive Motor	Suction Motor	Electric	Steam	in case of steam/thermal fluid heating	in case of electric heating			Shipping size (W x D x H) in mm
NXS-80 NXE-80	Ø 305 x 2134 (Ø 12" x 84")	4.66 RPM	2-5 RPM	0.37 KW	0.37 KW	9 KW	30 kg. per hr.	0.75 KW	9.75 KW	3" BSP (75mm)	3200 x 1350 x 1350	1450/1750 kg. 3400 x 1550 x 1450
NXS-83 NXE-83	Ø 458 x 2439 (Ø 18" x 96")	6.50 RPM	2-6 RPM	0.75 KW	0.75 KW	24 KW	72 kg. per hr.	1.50 KW	25.50 KW	3" BSP (75mm)	3500 x 1500 x 1350	2200/2650 kg. 3700 x 1700 x 1450
NXS-283 NXE-283	Ø 762 x 3048 (Ø 30" x 120")	10.1 RPM	3-10 RPM	3.75 KW	1.50 KW	72 KW	225 kg. per hr.	7.0 KW	77.25 KW	4" BSP (100mm)	4500 x 2040 x 1575	4500/4700 kg. 4700 x 2240 x 1675