



GANESH BENZOPLAST LTD.

POUR POINT DEPRESSANT- PPD (GL 3062)

TECHNICAL DATA SHEET

INTRODUCTION

A Pour Point Depressant for Lubricating Oils.

FORMULATION

Recommended at:

0.05% to 0.5% by weight or volume

GL 3051 is recommended for all lubricating oils where pour point reduction is the major objective. The recommended concentrations depend upon the performance desired and the response of the base oils.

TYPICAL INSPECTIONS CHARACTERISTICS

Physical Characteristics:

Specific Gravity @ 15.6 C (60 F)	0.92
Pounds per U.S. Gallon @ 60 F	7.4
Pounds per I.M.P. Gallon @ 60 F	8.88
Viscosity, cSt @ 100 C (210 F)	190
Viscosity, cSt @ 40 C	550



GANESH BENZOPLAST LTD.

POUR POINT DEPRESANT- PPD (GL 3062)

SPECIFICATION SHEET

TEST	PROCEDURE	MIN	MAX
1. PRIMARY ANALYSIS			
Specific Gravity @ 15.6° C	GL-GR-1	0.88	
Oil Blend Viscosity @ 100° C., cst	ASTM D 445	60	
Color, ASTM Dilute	ASTM D 1500		5
% Water	ASTM D 95	0.1	
Blot	GL-BL-1A		PASS
Clarity	CLARK CLAR.		PASS
Appearance		Clear	Liquid Viscous
2. SECONDARY ANALYSIS			
Viscosity @ 40° C., cst	ASTM D 445		550
Flash point, ° C., COC	ASTM D 92		150