

KDTA-D

DIGITAL TORQUE ANALYZERS FOR TORQUE DRIVERS



KDTA-80D

KDTA-8D / KDTA-80D

FEATURES

- Battery powered
- Checks any brand of electric driver
- Battery Charger with user selectable 100, 120 or 230V A/C adapter
- Lightweight plastic case
- kgf-cm/N-m / lb-in unit conversion

- MODE : RUN (constantly indicates torque value.)
PEAK HOLD
PEAK TO PEAK-HOLD
- AUTO RESET : Timer function available
- DATA OUTPUT : Digital output
- PRINTER : TPK-3 (Optional)
- Accuracy : $\pm 1\%$ of the indicated value + 1 increment, over the full range

Model	Range	Increment	Measuring mode	Battery	Size	Weight (g)
KDTA-8D	3-800mN-m 0.03-8kgf-cm 0.03-7lb-in	0.1mN-m 0.001kgf-cm 0.001lb-in	RUN Peak hold Peak to Peak hold	Rechargeable	120 (W) × 165 (D) × 64 (H) mm	830
KDTA-80D	3-800cN-m 0.3-80kgf-cm 0.3-70lb-in	0.1cN-m 0.01kgf-cm 0.01lb-in	RUN Peak hold Peak to Peak hold	Rechargeable	120 (W) × 165 (D) × 64 (H) mm	830

KDTA-NDEX

DIGITAL TORQUE ANALYZERS FOR ELECTRIC DRIVERS

KDTA-N10DEX / KDTA-N100DEX

FEATURES

- Battery is rechargeable.
- For any brand of the Electric Driver
- Battery Charger is available for AC100V~230V50/60H.

- MODE : RUN (constantly indicates torque value.)
PEAK HOLD
PEAK TO PEAK-HOLD
- AUTO RESET : Timer function available
- DATA OUTPUT : Digital output
- PRINTER : TPK-3 (Optional)



* Printer and printer cable are options.

Model	Range	Increment	Measuring mode	Battery	Size	Weight (g)
KDTA-N10DEX	1.5-100.0cN-m 0.15-10.00kgf-cm 0.13-10.00lbf-in	0.1mN-m 0.01kgf-cm 0.01lbf-in	RUN Peak hold Peak to Peak hold	Rechargeable	150 (W) × 110 (D) × 38 (H) mm	1,000
KDTA-N100DEX	1.5-1000cN-m 1.5-100.0kgf-cm 1.3-100.0lbf-in	1cN-m 0.1kgf-cm 0.1lbf-in	RUN Peak hold Peak to Peak hold	Rechargeable	120 (W) × 165 (D) × 64 (H) mm	1,000