

ITEM	PARAMETERS	SPECIFICATION
	Capacity	Free flow granular powder from 150cc to 1500cc
	Filling cups	Telescopic filling cups for one packsize will be provided with the machine
Operational Specifications	Volume control	Telescopic cups with adjustable volume for compensation of variation in bulk density
	No. Of heads	Two
	Operation mode	Manual -with two operators for two heads
	Filling speed	34 discharges per minute (17 discharges per minute on each side)
	Filling accuracy	+ 2% at constant powder level in the machine hopper and consistency of bulk density
	Powder feeding	To be arranged by you.
Drive	Motor	0.75 hp motor
	Gear box	Worm reduction gear box .
	Transmission	Through helical gearing.
	Machine hopper	60 litres.
	Dozer dies	5mm thick direct or 10mm thick machined ground dozer discs.
Physical specifications	Machine body	With heavy cast iron frames and top plate made from ss304. Guards made from ss304
	Discharge hopper	Discharge hopper with outlet diameter to suit the pouch mouth
	Moc	All parts coming in direct contact of the product made from s.s. 304. All other parts made m.s./ci powder coated /painted.
	Mounting	Suitable for table top mounting. Optional supporting frame available.
Overall dimensions	Main machine	1100mm x 850mm x 1300mm
	Supporting frame(optional)	650mm x 400mm x 900mm
	Net weight	300kgs approx