

## Technical Specifications

PARAMETERS	UNIT	MWMP120	MWMP160	MWMP200	MWMP250
OUTPUT CAPACITY	TPH	120	160	200	250
<b>FOUR BEEN FEEDER</b>					
Capacity	m <sup>3</sup>	30	36	36	45
Loading Width	mt.	3.21	3.7	3.7	3.7
Auxiliary Conveyor	mm/hp	500/2	500/3	500/3	500/3
Main Conveyor	mm/hp	600/5	600/5	600/5	750/7.5
Vibrator for fine Agg. Bin	hp	1	1	1	1
Connected Load	hp	14.5	20.5	20.5	20.5
<b>CHARGING CONVEYOR</b>	mm/hp	600/7.5	600/7.5	600/7.5	750/10
<b>PUGMILL (MIXER)</b>					
Capacity	m <sup>3</sup>	1.66	2	2.75	2.75
No. of Arms Pair	Pair	14 (28)	18 (36)	22 (44)	22 (44)
Connected Load	hp	25	30	40	50
<b>WATER PUMP</b>	hp	3	3	3	3
<b>HYD. POWER PACK</b>	hp	5	5	5	5
<b>GOB HOPPER</b> without Load out Conveyor	Ton	1	1*	1*	1*
<b>GOB HOPPER</b> with Load out Conveyor	Ton	1	1*	1*	1*
Load Out Belt Conveyor	mm	600	600	600	750
Connected Load	hp	5	5	5	7.5
<b>STORAGE SILO</b>	MT	25*	25	25	25
Load out Conveyor	mm	600	800	800	800
Connected Load	hp	7.5	15	15	15
<b>TOTAL CONNECTED LOAD</b>	hp	57.5	84	95	106.5
<b>OPTIONAL ACCESSORIES</b>					
<b>VIBRATING SCREEN</b>					
Screening Area	m <sup>3</sup>	1.1	1.1	1.1	1.1
Connected Load	hp	3	3	3	3
<b>WATER TANK</b>	Ltr.	10,000	15000	15000	15000

\*Optional: With MACONS policy of constant up gradation of products, design & specifications are subject to change without prior notice.