



SIVA INSTRUMENTS

An ISO 9001:2008 Company

Automatic Oil Insulation Test Kit

Model :OTS-PR-CG (100KV)

INTRODUCTION

The oil insulation test kit is intended to be used for testing of dielectric strength of insulating oil used in Transformer, Circuit breaker, CTs, PTs etc. The test kit is fully automatic and has the facility for Auto/Manual selections. The operator simply needs the sample in the test vessel & selects the required test. Testing can be done as per many international (IEC & European standards) which are programmed into the instrument memory. Stand time, stir times & rate of rise of applied voltage can be selected in Custom Mode also, one set of such selected mode can also be stored in the memory.

In addition to the above set can also perform withstand test (proof) tests. In this test the set allows the set voltage to pre-set value & hold for one minute to see if breakdown occurs. The backlit LCD is used for user friendly operations during the test process. It also display fault condition messages such as open ground cover open. All the user selected programmes are chosen through(4x3) key pad. The test results can be printed along with with test type, date, time, breakdown test voltage, averages and deviations. Voltage value can be measured & printed with a resolution of 0.1 kV. In reprint option it is possible to have number of printouts for the last test. For each test the readings are recorded and stored in memory. All stored readings can be transferred via the RS-232 interface to PC. A safety interlock prevents access to the high voltage terminals during testing. The design ensures a high level of safety for the operator. The high voltage chamber is covered by a polycarbonate door.



- ◆ FULLY AUTOMATIC MICRO CONTROLLER OPERATION.
- ◆ INTERNATIONAL STANDARD, PREPROGRAMMED

CUSTOM TESTS

- ◆ IEC156,ASTMD877'
- ◆ ASTMD1816,UNE21,IS: 6792
- ◆ STANDARDS (International)
- ◆ CUSTOM MODE
- ◆ WITHSTAND A
- ◆ WITHSTAND B
- ◆ 5 MINUTE TEST
- ◆ USER-PROGRAMMABLE WITH STAND (PROOF)TEST
- ◆ BACKLIT LCD DISPLAY
- ◆ BUILT IN PRINTER FOR TEST RESULTS



Automatic Oil Insulation Test Kit Model : OTS-PR-CG (100KV)

SPECIFICATIONS

Power Supply	: 250V AC +/-10%, 50Hz +/- 5 %, Single phase.
Voltage Range	: 0 to 100 KV AC
Trip Current	: 10mA (Custom Specs can be provided)
Indication	: 3 ½ Digit Panel Meter
Resolution	: 0.1KV in manual mode and 0.4KV in Auto mode
Accuracy	: ± 2% ± 2 Digits.
HV Transformer	: 50-0-50 KV with mid point earth , Double wound, air cooled, epoxy molded.
Variac	: Motorized.
Shut down Sensitivity	: 5mA
Shut Down Time	: < 20 milliseconds
Oil Test Cell	: Transparent polycarbonate moulded.
Gap Gauge	: 1mm /2mm / 2.5mm and 4mm.
Cabinet	: Powder coated sheet metal table top cabinet with lifting handles.
Controls	: Mains ON/OFF, HT ON/OFF, Hold, Stirrer ON/OFF, Timer ON/OFF, Auto/Manual Mode, reset switch.
Features	: Microprocessor control with following features Fully automatic Option to set a) Stand time. b) Stir time. c) Rate of rise of voltage 0.5 KV to 5KV adjustable d) No. of test carried out as per selected standard.
Printer	: Built-in-alphanumeric printer. Time & Dated result with standard deviation printed
Port	: RS 232c port interface to download data to PC.
Software	: Windows based Data Acquisition software.
Keypad	: Quick test selection through 12Keys soft touch Keypad .
Display	: Large Backlit LCD Display to display Test Menu, Set up Screens, TestResult.
Indications	: Cover Open, Wait time, HT On, KV rise, Stir time, Stand (Settle)Time, Temp. & BDV.
Beeps	: Audible beep on Breakdown & Long beep on completion of test.
Standards	: IEC 156, IS6792, ASTM D1816, ASTM D877, UNE 21, Withstand, Proof, Custom Modes.
Storage Memory	: 100 Test Results.
Safety Features	: Interlock on high voltage test chamber. Zero start protection. Double ground protection. All safety interlock to avoid shocks with indications. Protected against overloads & short circuits.
Safety Standards	: Meeting IEC 61010.
EMI/EMC Standards	: IEC/EN 61326
Accessories	: Mains Chord, Oil test vessels with adjustable electrodes.. GO NO GO Gauge for adjusting gap , Suitable Calibrator, Stirrer. Pairs of mushroom, Spherical & cylindrical electrodes and Transport case. Users/instruction manual.
Temperature Range	: Operating 0 50 °C
Humidity Range	: 80% Rh at 40 °C Storage 5 to 70 °C
Dimensions	: L=700 x B=320 x H=325 mm ± 10mm
Weight	: 50 Kg. Approx.

To keep pace with the latest technology Sivananda Electronics reserves the right to update it's system. Hence, information in this brochure is likely to change without notice.

SIVANANDA ELECTRONICS

DEEPAK MAHAL, LAM ROAD, DEVLALI-422 401, MAHARASHTRA, INDIA.

Phone: 0253-2491423, 2491504, 2491816, Fax: 0253-2492291. Email: mkb@sivanandaelenic.com

MUMBAI : 208, SAHAR PLAZA COMPLEX, ANDHERI KURLA ROAD, ANDHERI. MUMBAI-400059.

PHONE: 022-28271046, 66430590 / 91. FAX: 022-28389232. E-mail: sivabom@vsnl.com

NEW DELHI : G-145, KALKAJI, NEW DELHI-110 019. PHONE: 011-26221582, 26434442. E-mail: sivadel@hotwireindia.com

BANGALORE : 44/2, DICKENSON ROAD, BANGALORE-650 042. PHONE: 080-25585673, 25597416. E-mail: sivabl@vsnl.net

HYDERABAD : 102, ART PLAZA, YWCA LANE, NEAR HIRA HALL, BOGGUL KUNDA, ABIDS, HYDERABAD-500 001. PHONE: 040-2320943.

MFRS. OF ELECTRONIC INSTRUMENTS, METAL DETECTORS, TURNSTILES, PERIMETER PROTECTION SYSTEMS

Visit us at: www.sivanandaelectronics.com www.sivanandaelectro.com