

Specifications:

| Ref. | Ratchet ? | Torque Range | | | | Square Drive | | Length | Wt. |
|----------|--------------|--------------|---------|----------|---------|-----------------|------|--------|------|
| | | N.m | Kg.m | lbf.in | lbf.ft | in | mm | mm | mm |
| AVT100A | | 2.5-11 | 0.3-1.2 | 20-100 | 2-8 | 3/8 | 10 | 318 | 0.56 |
| AVT300A | | 5-33 | 0.5-3.4 | 40-300 | 4-24 | 3/8 | 10 | 422 | 0.71 |
| AVTR600 | | 12-68 | 1.2-7 | 100-600 | 10-50 | 3/8 | 10 | 476 | 1.02 |
| AVT600 | | 12-68 | 1.2-7 | 100-600 | 10-50 | 3/8 | 10 | 476 | 1.02 |
| EVT600A | | 12-68 | 1.2-7 | 100-600 | 10-50 | 1/2 | 12.5 | 476 | 1.02 |
| EVT1200A | | 25-135 | 3-14 | 200-1200 | 20-100 | 1/2 | 12.5 | 546 | 1.62 |
| EVTR1200 | | 25-135 | 3-14 | 200-1200 | 20-100 | 1/2 | 12.5 | 555 | 2.00 |
| EVT2000A | | 50-225 | 5-23 | 400-2000 | 40-160 | 1/2 | 12.5 | 597 | 2.38 |
| EVT3000A | | 70-330 | 7-35 | 600-3000 | 50-250 | 1/2 | 12.5 | 825 | 3.12 |
| EVTR3000 | | 70-330 | 7-35 | 600-3000 | 50-250 | 1/2 | 12.5 | 840 | 4.00 |
| HVT5000 | | 140-560 | | | 100-410 | 3/4 | 20 | 1130 | 6.58 |
| HVT7200 | | 200-8 | | | 150-6 | 3/4 | 20 | 1181 | 7.00 |

| | | | | | | | | | |
|----------|--|-------------|--|--|-------------|-----|----|------|-------|
| | | 10 | | | 00 | | | | |
| GVT8400 | | 480-9 40 | | | 350-7 00 | 1 | 25 | 1397 | 12.70 |
| HVTR5000 | | 140-5 60 | | | 100-4 10 | 3/4 | 20 | 1210 | 5.90 |
| HVTR7200 | | 200-8 10 | | | 150-6 00 | 3/4 | 20 | 1261 | 6.50 |
| GVTR8400 | | 480-9 40 | | | 350-7 00 | 1 | 25 | 1471 | 11.30 |