

Model	Capacity Dry Wt Per Charge	Basket Dia x Depth	Tank	Capacity (Lt.) Distillator / Nylon Filter	Drive Motor Washing Drive Motor Extracting	Pump / Fan Refrigerator Air Compressor	Heating EL Distillator / Air Heater	Steam Power Electric Power	Steam Compressed Air Water	Consumption With/without distillation Water (lt./cycle) Steam(kg/hr.) Electricity (Kwh)	Connection Air/ Water Inlet/ Water Outlet/ Steam Inlet/ Condensate Outlet	Dimension Width Depth Height	Net Weight/Shipping Wt. Shipping Size (WxDxH) Shipping Volume
		Volume/Door Dia.											
PM-200	10 / 12	700 x 520	135	160/35	2.2 KW	0.55 KW / 1.1KW 2.0 KW	7.5 KW	6 KW	4.5	140(45)	1/4"	1600	950 / 2090
		200 / 420			2.2 KW	0.35 KW	4.2 KW	18 KW	6 1.5+6	40(15) 6.7(1.3)	1/2" / 1/2" 1/2" / 1/2"	1400 1940	
PM-300	15 / 17	850 x 530	115	160/35	2.2 KW	0.55 KW / 1.1KW 2.2 KW	7.5 KW	6 KW	4.5	140(45)	1/4"	1600	980 / 2156
		300 / 420			2.2 KW	0.35 KW	4.2 KW	18 KW	6 1.5+6	50(22) 6.9(1.6)	1/2" / 1/2" 1/2" / 1/2"	1420 1980	
PM-360	18 / 20	900 x 565	115	160/35	2.2 KW	0.55 KW / 2.1KW 2.2 KW	7.5 KW	7 KW	4.5	150(50)	1/4"	1600	1040 / 2288
		360 / 420			2.2 KW	0.35 KW	4.8 KW	19.5 KW	6 1.5+6	50(22) 7.2(1.7)	1/2" / 1/2" 1/2" / 1/2"	1420 1980	
PM-400	20 / 22	1000 x 520	140	215/50	2.2 KW	0.55 KW / 2.2KW 2.2 KW	12.0 KW	7 KW	5	180(80)	1/4"	2080	1550 / 2680
		408 / 420			2.2 KW	0.35 KW	4.8 KW	24 KW	8 2 / 6	70(40) 10(3.2)	1/2" / 1/2" 1/2" / 1/2"	1450 2070	
PM-500	25 / 28	1060 x 570	180	300/66	3.5 KW	0.55 KW / 2.2KW 3.0 KW	16 KW	9.5 KW	5	190(100)	1/4"	2250	2000 / 4450
		503 / 520			3.5 KW	0.35 KW	4.8 KW	31 KW	8 2 / 6	90(50) 13.3(8)	1/2" / 1/2" 1/2" / 1/2"	1680 2130	
PM-700	33 / 35	1060 x 750	180	330/66	4.0 KW	1.0 KW / 1.5KW 1.5 KW	16 KW	14 KW	5	190(100)	1/4"	2250	2800 / 6150
		670 / 520			4.0 KW	0.35 KW	7.5 KW	35 KW	8 2 / 6	90(50) 14.3(9)	1/2" / 1/2" 1/2" / 1/2"	1700 2240	