

MODEL	CAPACITY	BASKET SIZE	DRIVE MOTOR	AIR DELIVERY	LOADING DOOR OPENING	HEATING (Options)				OVERALL DIMNS. (W x D x H)	NETT. WT./SHIPPING WT. SHIPPING SIZE (WxDxH) SHIPPING VOLUME
		VOLUME	BLOWER MOTOR	AIR OUTLET		STEAM CONNECTION CONSUMPTION	ELECTRIC	THERMAL FLUID CONNECTION CONSUMPTION	INDIRECT DIESEL FIRED CONSUMPTION		
NXS - 15 NXE - 15 NXF - 15	15 Kg.	900 Ø x 600	0.75 KW	1500 ft <sup>3</sup> /Hr.	550	15 Ø (.5" BSP) 20 Kg./Hr.	9-12 KW	0.5" x 0.5" BSP 10000 K.Cal./Hr.	N. A.	1000 x 1240 x 1920	350 Kg. / 500 Kg. 1300 x 1540 x 2120 4.25 M <sup>3</sup>
		380 Ltrs.	0.75 KW	225 Ø							
NXS - 30 NXE - 30 NXF - 30 NXD - 30	30 Kg.	950 Ø x 950	0.75 KW	1500 ft <sup>3</sup> /Hr.	640	15 Ø (.5" BSP) 40 Kg./Hr.	18-24 KW	0.5" x 0.5" BSP 15000 K.Cal./Hr.	1.5-2 Ltrs. per Hr.	1050 x 1540 x 1980	600 Kg. / 825 Kg. 1350 x 1840 x 2180 5.4 M <sup>3</sup>
		670 Ltrs.	0.75 KW	225 Ø							
NXS - 60 NXE - 60 NXF - 60 NXD - 60	60Kg.	1250 Ø x 990	1.5 KW	3000 ft <sup>3</sup> /Hr.	750	20 Ø (.75" BSP) 60-80 Kg./Hr.	36-48 KW	1" x 1" BSP 40000 K.Cal./Hr.	2.5-3.5 Ltrs. per Hr.	1350 x 1690 x 2300	950 Kg. / 1250 Kg. 1650 x 2000 x 2500 8.25 M <sup>3</sup>
		1214 Ltrs.	1.5 KW	300 Ø							
NXS - 120 NXF - 120 NXD - 120	120 Kg.	1600 Ø x 1200	1.5 KW	6000 ft <sup>3</sup> /Hr.	825	20 Ø x 2 Nos. or 25 Ø x 1 No. 100-150 Kg./Hr.	N. A.	1.5" x 1.5" BSP 80000 K.Cal./Hr.	5.5-6.5 Ltrs. per Hr.	1750 x 2050 x 2720	2050 Kg. / 2550 Kg. 2050 x 2350 x 3000 14.45 M <sup>3</sup>
		2411 Ltrs.	1.5 KW x 2 Nos.	300 Ø x 2							
NXS - 240 NXF - 240 NXD - 240	240 Kg.	2000 Ø x 1450	5.5 KW	12000 ft <sup>3</sup> /Hr.	1250	20 Ø x 2 Nos. or 25 Ø x 1 No. 200-250 Kg./Hr.	N. A.	2" x 2" BSP 1,60000 K.Cal./Hr.	11-16 Ltrs. per Hr.	2180 x 2750 x 3250	4570 Kg. / 5050 Kg. 3140 x 2930 x 3150 29 M <sup>3</sup>
		4553 Ltrs.	3.75 KW x 2 Nos.	370 Ø x 2							