

ST96 LCR Meter



- * New type holster, streamline design.
- * Large LCD makes the reading clearly.
- * Metallic screen board with stronger antimagnetic and anti-interferential function.
- * Buzzer alarm, data hold, Diode and Transistor test function.

The Salicon hand held ST96 3 1/2 digital L/R meter is compact general purpose Digital Multimeter. Its rugged engineering design with protective holster makes it. Choice for reliable partner in measurements, be at test bench or, at shop floor. ST96 is supplied with Probe as accessory.

Inductance

Range	Accuracy	Resolution	measuring frequency
2mH	$\pm (2.0\%+5d)$	1uH	Approx : 200 Hz
20mH	$\pm (2.0\%+5d)$	10uH	
200mH	$\pm (2.0\%+5d)$	100uH	
2H	$\pm (5.0\%+5d)$	1mH	Approx : 200 Hz
20H	$\pm (5.0\%+15d)$	10mH	Approx : 200 Hz

Capacitance

Range	Accuracy	Resolution	measuring frequency
2nF	$\pm (1.0\%+5d)$	1pF	Approx : 200 Hz
20nF	$\pm (1.0\%+5d)$	10pF	
200nF	$\pm (1.0\%+5d)$	100pF	
2uF	$\pm (2.0\%+5d)$	1pF	Approx : 200 Hz
20uF	$\pm (2.0\%+5d)$	10pF	Approx : 16 Hz
200uF	$\pm (5.0\%+5d)$	100pF	Approx : 16 Hz
1000uF	$\pm (5.0\%+25d)$	1pF	Approx : 8 Hz

Resistance

Range	Accuracy	Resolution
200Ω	$\pm (0.8\%+5d)$	0.1Ω
2kΩ	$\pm (0.8\%+3d)$	1Ω
20kΩ	$\pm (0.8\%+3d)$	10Ω
200k	$\pm (0.8\%+3d)$	100Ω
2MΩ	$\pm (0.8\%+3d)$	1kΩ
20MΩ	$\pm (1.0\%+15d)$	10kΩ

Salicon Nano Technology Pvt. Ltd.

111, 1st Floor, Laxmi Deep Tower, Laxmi Nagar District Center, Delhi - 110092, INDIA,
 Tel: 91-11-22525940, 40618940; Fax; 91-11-22525941; E-mail: info@salicontech.com; Web: www.salicontech.com