

SAMPLING SYSTEM WITH INDICATOR



SPECIFICATIONS:

- | | |
|--|--|
| <ul style="list-style-type: none"> ▣ One Moisture Transmitter - ▣ Range ▣ Resolution--- ▣ Accuracy----- ▣ Display: ----- ▣ Sensor Connections-- ▣ Calibration --- ▣ Power supply-- ▣ Outputs: ▣ Sampling system (indigenous): ▣ Cabinet: ▣ Operational Area: - | <p>High capacitance Al₂O₃
 , -100°C / +20°C DP Or -65°C / +20°C
 0.1°C DP
 +/- 2 deg C Dew point
 LED digital indicating meter showing Dew point Deg. C only.
 Low loss co-ax cable
 Manual cal
 mains 230V ac,
 4-20mA & Alarms: 1 Relays contact</p> <p>sensor holder, flow control, Rota meter, 1/8 "input output fitting mounted on panel with
 Local led indicator in dew point -^oc</p> <p>Table mount /Panel mount
 Safe Area.</p> |
|--|--|

◆ In the interest of continued product we reserve the right to change the specification without prior notice

Hemaki
LAB-SERVICES

252-D Amar Gian Industrial Estate, L..B.S. Marg, Khopat, Thane (W) 400 6
Maharashtra, India Tel. +91 (022) 2547 49 01 Telefax : 2547 58 68
Email : hemaki@vsnl.com Web site : www.hemaki.com