

CHARACTERISTICS	UNIT	IX-2	IR-3	IR-7	IR-10	IX-20	IX-35	IX-47	IN -30	IN-50
Capacity	ltr	1.6	3.9	7.8	10.5	20.5	34	47	30	50
Static Evaporation Loss Rate	ltr/day	0.08	0.14	0.11	0.12	0.1	0.11	0.37	0.28	0.43
Static Holding Time	day	20	29	68	90	211	288	127	107	116
Working Time	day	12.5	18	42	56	132	180	79	-	-
Total Height	mm	390	433	495	570	695	710	635	560	740
Overall Diameter	mm	163	224	260	260	380	432	430	432	432
Neck Tube Diameter	mm	34.5	51	51	51	51	51	120	51	51
Empty Weight	kg	1.8	2.7	4.5	5	10.7	14.3	18	11.3	14.8
Full Weight	kg	3.2	6.3	11.5	14	28	41.5	51.5	37	53.5
No. of Canisters	pcs	5	6	6	6	6	6	11	-	-
Canister OD	mm	25	38	38	38	38	38	72	-	-
Canister Height	mm	120	120	120	120/230	120/230	120/280	230	-	-
Straw Holding Capacity Single Level 0.25 ml	pcs	600	1560	1560	1560	1560	1560	-	-	-
0.5 ml	pcs	290	720	720	720	720	720	-	-	-
Straw Holding capacity Double Level 0.25 ml	pcs	-	-	-	3120	3120	3120	18000	-	-
0.5 ml	pcs	-	-	-	1440	1440	1440	8000	-	-