

MODEL	CAPACITY	BASKET SIZE (DIA X DEPTH)	LOADING DOOR OPENING	Drive motor	WATER CONNECTION	DRAIN	HEATING				OVERALL DIMENSIONS (W X D X H)	NET WT./SHIPPING WT. SHIPPING SIZE (W X D X H) SHIPPING VOLUME
		VOLUME	NO. OF DOOR		WATER CONSUMPTION PER DIP IN LTRS.		STEAM CONNECTION	ELECTRIC	DIESEL FIRED	THERMIC FLUID CONN.		
							CONSUMPTION		TEMP. RAISE PER MINUTE	CONSUMPTION		
NXS-12 NXE-12 NXD-12	12 KG.	550 Ø X 720 170 LTRS.	400 X 300 1	0.37 KW	1" BSP	3" (75MM)	15 MM (0.5" BSP)	6-12 KW	1-1.5 LTRS.	N.A.	1790 X 760 X 1100	500 KG./700 KG. 2000 X 960 X 1200 2.3 M ³
					85		8-10 KG./HR.					
NXS-30 NXE-30 NXD-30	30 KG.	750 Ø X 950 419 LTRS.	520 X 400 1	0.75 KW	1.5" BSP	3" (75 MM)	15 MM (0.5" BSP)	12-18 KW	1.5-2 LTRS. DIESEL PER HR. TEMP. RISE 2° C PER MINUTE	N.A.	2050 X 965 X 1310	800 KG./1000 KG. 2250 X 1265 X 1535 3.8 M ³
					210		15-20 KG./HR.					
NXS-65 NXE-65 NXF-65 NXD-65	65 KG.	950 Ø X 1270 900 LTRS.	665 X 450 1	2.25 KW	2" BSP	4" (100 MM)	15 MM (0.5" BSP)	24 KW	3-4 LTRS. DIESEL PER HR. TEMP. RISE 2° C PER MINUTE	1" X 1" 22000 KCAL/HR.	2460 X 1200 X 1325	1000 KG./1200 KG. 2680 X 1400 X 1425 5.35 M ³
					450		30-40 KG./HR.					
NXS-80 NXE-80 NXF-80 NXD-80	80 KG.	1060 Ø X 1270 1120 LTRS.	665 X 470 1	3.75 KW	2" BSP	4" (100 MM)	15 MM (0.5" BSP)	36 KW	4-5 LTRS. DIESEL PER HR. TEMP. RISE 2° C PER MINUTE	1" X 1" 27000 KCAL/HR.	2600 X 1310 X 1400	1100 KG./1400 KG. 2850 X 1650 X 1630 7.65 M ³
					540		50-60 KG./HR.					
NXS-100 NXE-100 NXF-100 NXD-100	100 KG.	1150 Ø X 1380 1432 LTRS.	665 X 470 1	5.62 KW	2" BSP	4" (100 MM)	15 MM (0.5" BSP)	36 KW	5-6.5 LTRS. DIESEL PER HR. TEMP. RISE 2° C PER MINUTE	1" X 1" 43000 KCAL/HR.	2775 X 1400 X 1580	1300 KG./1550 KG. 3015 X 1630 X 1820 8.95 M ³
					700		60-80 KG./HR.					
NXS-150 NXF-150 NXD-150	150 KG.	1060 Ø X 2440 2150 LTRS.	665 X 470 2	7.5 KW	2" BSP X 2 NOS.	6" (150 MM)	20 MM X 2 NOS. (0.75" BSP)	N.A.	7-8 LTRS. DIESEL PER HR. TEMP. RISE 2° C PER MINUTE	1.5" X 1.5" 65000 KCAL/HR.	3925 X 1310 X 1400	1750 KG./2150 KG. 4155 X 1650 X 1630 11.17 M ³
					1060		100-120 KG./HR.					
NXS-200 NXF-200 NXD-200	200 KG.	1220 Ø X 2440 2850 LTRS.	665 X 470 2	11.25 KW	2" BSP X 2 NOS.	6" (150 MM)	20 MM X 2 (0.75" BSP)	N.A.	8-10 LTRS. DIESEL PER HR. TEMP. RISE 2° C PER MINUTE	1.5" X 1.5" 95000 KCAL/HR.	3925 X 1470 X 1610	2350 KG./3000 KG. 4155 X 1700 X 1850 13.1 M ³
					1400		160-180 KG./HR.					