

MODEL	NGL 16mm	NGL 18mm	NGL 20mm	NGL 24mm	NGL 26mm	NGL 30mm	NGL 36mm	NGL 40mm	NGL 48mm	NGL 60mm
Length of Bed	4900	5500	6100	7300	7900	9150	10970	12200	14600	18300
Width of Bed	650	700	750	800	900	1000	1050	1150	1250	1500
Height of Center	600	650	700	750	850	950	1000	1100	1150	1350
Distance Between Center	2850	3450	4050	5150	5750	6800	8500	9600	11700	15000
Spindle Hollow	103	103	103	103	103	103	127	150	150	150
Swing over Saddle (Dia)	950	1050	1100	1150	1400	1600	1650	1850	1950	2350
Swing Over Bed (Dia)	1200	1300	1400	1500	1700	1900	2000	2200	2300	2700
Swing Over Gap (Dia)	1700	1800	1900	2000	2200	2400	2500	2700	2800	3250
No. of Spindle Speeds	8	8	8	8	8	8	8	8	8	8
RPM Range	3-85	3-85	3-85	3-85	3-85	3-85	3-85	3-85	3-85	3-85
Lead Screw Dia	60	60	60	60	60	75	80	85	85	85
Lead Screw Pitch T.P.I.	2	2	2	2	2	2	2	2	2	2
H.P. Recommended	7.5	10	10	15	20	20	25	30	30	20