

# TECHNICAL SPECIFICATIONS

## STATIONARY BATTERIES STANDBY POWER

### LOW MAINTENANCE (LM)

Type	Voltage	Capacity - AH		Dimensions (MM)			Weights (kg)		Volume of Electro- lyte - Liters  (Approx.)
		10 Hrs 1.85 V/ Cell	100Hrs 1.90 V/ Cell	L  +/-5	W  +/-5	H  max	Dry	Filled	
<b>2 V CELLS IN P.P CONTAINERS</b>									
2AP-100	2V	100	145	103	206	430	9.0	14.0	4.8
2AP-150	2V	150	218	103	206	430	11.1	16.4	4.3
2AP-200	2V	200	290	103	206	430	13.3	18.9	4.0
2AP-250	2V	250	363	124	206	430	15.5	21.7	5.0
2AP-300	2V	300	435	145	206	430	18.5	25.9	6.1
2AP-350	2V	350	508	124	206	550	20.1	27.3	6.0
2AP-420	2V	420	609	145	206	550	24.0	31.9	6.6
2AP-490	2V	490	711	166	206	550	28.1	36.6	7.1
2AP-600	2V	600	870	145	206	700	34.4	47.7	10.7
2AP-800	2V	800	1160	191	210	700	47.9	64.9	13.7
2DS-1000	2V	1000	1450	233	210				