



Specification :

Process Connection	Threaded or Flanged
Connection Size	1/2" or 3/4" BSP(M) or Flanged to 3/4" or 1" ASA 150 Lbs as standard (Please specify other connections ,if required)
End Connection MOC (Wetted Parts)	Mild Steel Grey powder coated / Chromium plated MS / SS 304 / SS316 / PVC/ FRP
Gauge Glass	19 mm H/W borosilicate glass tube.
Glass Tube Protection	C-Channel of Grey powder coated or Chromium plated MS / SS304 / FRP Or SS316. (Size: 45x65x2mm)
Flange Gaskets	CAF-Acid alkali style 60
Scale	Black powder coated aluminium with white numerals & markings.
Vent& Drain Plugs	1/2" BSP(M)
Bolts & Nuts	HT bolts & nuts/SS 304
Maximum working pressure-10 kg/sq.cm (depends on length)	
Maximum working temperature-100 deg C (Maximum length in single piece-2500 mm)	

Optional Accessories :

- **Vent Cock Valve/Drain Cock/Vent & Drain Needle/Ball Valves**
- **Gauge Isolating Needle Valves.**
- **Gauge isolator valve: SS 304/316 solid barstock needle valve,offset type with safety ball-check protection and process connection as above (please specify).**