

ITEM	PARAMETERS	SPECIFICATION
	Filling capacity	Free flow grannular powder from 150cc to 1500cc
	Filling cups	Telescopin filling cups for one packsize will be provided with the machine
Operational Specification	Volume control	Telescopic cups with adjustable volume for compensation of variation in bulk density
	No. Of heads	one
	Operation mode	Manual -with one operators for one heads
	Filling speed	17 dischsges per- minute on each side
	Filling accuracy	+ 2% at constant powder level in the machine hopper and consistency of bulk density
	Powder feeding	To be arranged by you.
Drive	Motor	0.75 hp motor
	Gear box	worm reduction gear box
	Transmission	Through helical and bevel gearing.
	Machine hopper	30 litres.
	Dozer dies	10mm thick machined ground dozer discs.
	Machine body	With heavy cast iron frames and top plate made from ss304. Guards made from ss304
	Discharge hopper	Discharge hopper with outlet diameter to suit the pouch mouth
Physical specification	Moc	All parts coming in direct contact of the product made from s.s. 304. All other parts made m.s./ci powder coated /painted.
	Mounting	Suitable for table top mounting. Optional supporting frame available.
Overall dimensions	Main machine	1100mm x 850mm x 1300mm
	Supporting frame(optional)	650mm x 400mm x 900mm
	Net weight	250kgs approx